




Tyria Lighting Technology Co.,Ltd




Baoguang Building, Fuyong Avenue, Fuyong Town, Baoan District, Shenzhen, Guangdong, China

Tel: +86 18938693458 Fax: +86 755 3693 1652

Contact: Janice Liu Email: janiceliu@tyrialight.com Web: www.tyrialight.com

Adjustable CCT LED Panel Light

No.	Part No.	Photo	Specifications		Packaging information
1	TY-PL0303-16W-CCT	<p>300*300mm - 16W</p> 	<p>Size: 300*300*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 336pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 16W Luminous Flux(lm): 1200-1500LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 1.50kg/pcs G.W.: 8.0kg/ctn Inner Box Size: 40*30*2cm Carton Size: 42*42*17cm 5pcs/carton</p>
2	TY-PL0603-18W-CCT	<p>600*300mm - 18W</p> 	<p>Size: 600*300*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 352pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 18W Luminous Flux(lm): 1300-1600LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 2.90kg/pcs G.W.: 16.0kg/ctn Inner Box Size: 72*39*2cm Carton Size: 73*42*17cm 5pcs/carton</p>
3	TY-PL0505-30W-CCT	<p>500*500mm - 30W</p> 	<p>Size: 500*500*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 576pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 30W Luminous Flux(lm): 2300-2800LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 4.80kg/pcs G.W.: 24.80kg/ctn Inner Box Size: 72*69*2cm Carton Size: 73*70*17cm 5pcs/carton</p>

No.	Part No.	Photo	Specifications		Packaging information
4	TY-PL0606-36W-CCT	<p>600*600mm - 36W</p> 	<p>Size: 600*600*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 720pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 36W Luminous Flux(lm): 2700-3200LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 4.80kg/pcs G.W.: 24.80kg/ctn Inner Box Size: 72*69*2cm Carton Size: 73*70*17cm 5pcs/carton</p>
5	TY-PL6262-36W-CCT	<p>620*620mm - 36W</p> 	<p>Size: 620*620*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 704pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 36W Luminous Flux(lm): 2700-3200LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 4.80kg/pcs G.W.: 24.80kg/ctn Inner Box Size: 72*69*2cm Carton Size: 73*70*17cm 5pcs/carton</p>
6	TY-PL1203-36W-CCT	<p>1200*300mm - 36W</p> 	<p>Size: 1200*300*11mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 720pcs, SMD3014 LED Chip: Lumenmax high brightness LED Watt(W): 36W Luminous Flux(lm): 2700-3200LM CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz CCT(K): WW(2700~3300K),NW(4000-4500K),CW(6000-6500K) Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 5.10kg/pcs G.W.: 23.50kg/ctn Inner Box Size: 128*38.5*5cm Carton Size: 130*41*28cm 4pcs/carton</p>