




Tyria Lighting Technology Co.,Ltd



Baoguang Building, Fuyong Avenue, Fuyong Town, Baoan District, Shenzhen, Guangdong, China

Tel: +86 18938693458 Fax: +86 755 3693 1652

Contact: Janice Liu Email: janiceliu@tyrialight.com Web: www.tyrialight.com

RGB LED Panel Light

No.	Part No.	Photo	Specifications		Packaging information
1	TY-PL0303-8W-RGB	<p>300*300mm - 8W</p> 	<p>Size: 295*295*12.5mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 30pcs, SMD5050 LED Chip: Epistar high brightness LED Watt(W): 8W Luminous Flux(lm): 1800-2000mcd/led CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz Output Voltage(V): DC 12V Color: RGB Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 1.50kg/pcs G.W.: 8.0kg/ctn Inner Box Size: 40*30*2cm Carton Size: 42*42*17cm 5pcs/carton</p>
2	TY-PL0603-16W-RGB	<p>600*300mm - 16W</p> 	<p>Size: 595*295*12.5mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 66pcs, SMD5050 LED Chip: Epistar high brightness LED Watt(W): 16W Luminous Flux(lm): 1800-2000mcd/led CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz Output Voltage(V): DC 12V Color: RGB Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 2.90kg/pcs G.W.: 16.0kg/ctn Inner Box Size: 72*39*2cm Carton Size: 73*42*17cm 5pcs/carton</p>
3	TY-PL0606-30W-RGB	<p>600*600mm - 30W</p> 	<p>Size: 595*595*12.5mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 132pcs, SMD5050 LED Chip: Epistar high brightness LED Watt(W): 30W Luminous Flux(lm): 1800-2000mcd/led CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz Output Voltage(V): DC 12V Color: RGB Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 4.80kg/pcs G.W.: 24.80kg/ctn Inner Box Size: 72*69*2cm Carton Size: 73*70*17cm 5pcs/carton</p>

No.	Part No.	Photo	Specifications		Packaging information
4	TY-PL1203-30W- RGB	<p>1200*300mm - 30W</p> 	<p>Size: 1195*295*12.5mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 132pcs,SMD5050 LED Chip: Epistar high brightness LED Watt(W): 30W Luminous Flux(lm): 1800-2000mcd/led CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz Output Voltage(V): DC 12V Color: RGB Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 5.10kg/pcs G.W.: 23.50kg/ctn Inner Box Size: 128*38.5*5cm Carton Size: 130*41*28cm 4pcs/carton</p>
5	TY-PL1206-48W- RGB	<p>1200*600mm - 48W</p> 	<p>Size: 1195*595*12.5mm Lamp housing material: PMMA shell and Aviation Aluminum 6063 LED QYT: 198pcs,SMD5050 LED Chip: Epistar high brightness LED Watt(W): 48W Luminous Flux(lm): 1800-2000mcd/led CIR(Ra): 75-80</p>	<p>Input Voltage(V): AC80-265V 50-60Hz Output Voltage(V): DC 12V Color: RGB Lifespan(hrs): ≥50000 Working temperature(°C): -20~+40 Storage Temperature(°C): -20~+65 Warranty: 3 years Certificate: UL.FC.GS.PSE.CE,ROHS</p>	<p>G.W.: 10.70kg/pcs G.W.: 45.80kg/ctn Inner Box Size: 128*69*5.5cm Carton Size: 130*72*25cm 4pcs/carton</p>